

for GAS  
according to EN 437

No. 5265

## HAKU Saddle

**For PE of all pressure ratings,  
(DIN 8075, ÖNORM B 5192) up to PN 4**

**with female thread ISO 228-1 and male thread DIN 259  
for bagging-off equipment - with plug and cap**

**Plug** - with an O ring for stress free inner seal  
and 22 mm square head

**Cap** - for covering the male thread

Pipe Ø mm	threaded outlet female thread 2" male thread 2 1/2"
90	●
110	●
140	●
160	●
225	●

The HAKU sealing system is the best method for sealing outlets in plastic pipes.

The HAKU seal is in full contact with the entire diameter of the PE pipe and is glued into the saddle for ease of installation.

In addition two concentric lip seals surround the outlet thus relieving the pressure upon the drill hole and protecting it from deformation.



**Material:**

Saddle body:	ductile iron - EN 1563 epoxy powder coated
Plug and cap:	ductile iron - EN 1563 galvanized
Seals:	elastomer - DIN 3535
Bolts:	stainless steel - A 2 DIN 933

Pipe Ø	d Ø	H	L	L 1	Weight kg
90	57	82	150	110	3,7
110	57	92	170	120	4,6
140	57	108	208	120	5,3
160	57	118	230	120	7,7
225	57	150	310	120	9,5

