



**Product Specification**  
**Pipelines & Fittings**  
**DENSO ACRYLIC TOP COAT**

- DESCRIPTION:** A pigmented, water borne, gloss acrylic coating, **FOR THE TOPCOATING OF DENSO ULTRASEAL TAPE.**
- COLOURS:** Standard Colours: White and Lt. Aircraft Grey
- APPLICATION:** Do not apply below 10°C or above 30°C or when relative humidity exceeds 90%. May be applied by brush or roller.
- PHYSICAL PROPERTIES:**
- |                            |   |
|----------------------------|---|
| <u>Flash Point:</u>        | Not applicable.   |
| <u>Volume Solids:</u>      | 38%.  |
| <u>Drying/Curing Time:</u> | Touch dry - 30 minutes at 20°C. Recoat in 2 hours at 20°C. Handle when dry. |
- SHELF LIFE:** Minimum 12 months if stored in sealed container below 35°C.
- POT LIFE:** Not Applicable.
- MIXING:** Stir thoroughly to achieve a homogeneous mix.
- THINNING:** Use only clean water.
- THEORETICAL COVERAGE:**
- 3.0m<sup>2</sup>/litre
- PACKAGING:** Supplied in 4 litre and 20 litre containers.
- HEALTH AND SAFETY:**
- Wear protective clothing and ensure adequate ventilation. Avoid contact with skin and eyes. Health and Safety Data Sheets giving full information are available.
- PACKAGING:** Supplied in 4 litre units.