



LEADERS IN CORROSION PREVENTION AND SEALING TECHNOLOGY

TECHNICAL DATA SHEET



Certificate No. FM 01548 BS EN ISO 9001:2000

REF: TDS132/05.01

DENSO PRIMING SOLUTION

DESCRIPTION Denso Priming Solution is a brush or spray applied primer intended for large areas prior to the application of petrolatum tapes and compounds.

COMPOSITION Petrolatum in aromatic hydrocarbon solvent

TYPICAL PROPERTIES	DATA
Specific Gravity	0.89
Covering Capacity	9m ² /litre
Dry Film Thickness	50 micron average
Viscosity BS/B4 CUP @ 25°C	55-70 seconds
Drying Time	60 minutes approx.
Flash Point	32°C minimum
Application Temperature Range	-20°C to 55°C

SURFACE PREPARATION	Surfaces must be dry and free from loose rust, scale or flaking coatings by wire brushing to Swedish standard St2 or grit blasting.
----------------------------	---

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd, Denso House, Chapel Road, London SE27 0TR, United Kingdom
Tel: +44 (0) 20 8670 7511 Fax: +44 (0)20 8761 2456 Email: mail@denso.net Website: www.denso.net