



## DENSOBAND PRIMER

**DESCRIPTION**      A fast drying bitumen based primer for all surfaces prior to the application of DensoBand, Denso Overbanding Tape and Denso Paving Tape.

**COMPOSITION**      Oxidised bitumen in aliphatic and aromatic hydrocarbon solvents

TYPICAL PROPERTIES	DATA
Specific Gravity	0.940
Covering Capacity	7-8m <sup>2</sup> /litre (1 litre per 150m x 50mm)
Wet Film Thickness	125-140 micron
Dry Film Thickness	70-80 micron
Drying Time	10-15 minutes
Flashing Point	23°C minimum
Application Temperature Range	0°C to 55°C

<b>SURFACE PREPARATION</b>	Surfaces must be dry and free from dust and loose material. Sweep or brush well before applying primer.
----------------------------	---

<b>PACKING</b>	5 litre and 25 litre metal containers
----------------	---------------------------------------

**Important**

*Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.*

*Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (Certificate No. FM01548).*

**Winn & Coales (Denso) Ltd**  
 Denso House, Chapel Road,  
 London SE27 0TR, United Kingdom



**Tel: +44 (0) 20 8670 7511**  
**Fax: +44 (0) 20 8761 2456**  
**Email: mail@denso.net Web: www.denso.net**