



## DENSO FLASHING TAPE PRIMER

**DESCRIPTION** A brush applied solvent-based primer. Used for priming surfaces prior to the application of Denso Flashing Tape.

**COMPOSITION** Solution of oxidised bitumen in aromatic hydrocarbon solvent.

TYPICAL PROPERTIES	DATA
Specific Gravity	0.94
Flash Point (c.c.)	23°C minimum
Solids Content	58% w/w
Covering Capacity	7-8m <sup>2</sup> /litre
Application Temperature	0°C-55°C
Drying Time	20-30 minutes

<b>PACKING</b>	Plain tinplate lever lid tins, 1 litre
----------------	--

<b>CLEANING SOLVENT</b>	White spirit
-------------------------	--------------

### Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd  
Denso House, Chapel Road,  
London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511  
Fax: +44 (0) 20 8761 2456  
Email: [mail@denso.net](mailto:mail@denso.net) Web: [www.denso.net](http://www.denso.net)