



## DENSO CLEAR PRIMER

**DESCRIPTION**      A clear, fast drying rubber/resin based primer for iron, steel, concrete or asphalt surfaces prior to the application of Tokstrip, Densoband, Denso Overbanding Tape and other bitumen based products to give a cleaner final appearance.

**COMPOSITION**      Blend of rubber and resins in aromatic hydrocarbon solvent. It contains a pink dye to indicate where it is applied which fades in sunlight.

TYPICAL PROPERTIES	DATA
Colour	Clear Pink
Specific Gravity	0.9
Covering Capacity	6-8m <sup>2</sup> /litre
Drying Time	10-15 minutes
Flash Point	23°C MIN
Application Temperature Range	5°C to 50°C

<b>SURFACE PREPARATION</b>	Surfaces to be clean, dry and free from dust laitance etc. Sweep or brush well before applying primer.
----------------------------	--

<b>APPLICATION METHOD</b>	Brush or roller.
---------------------------	------------------

<b>CLEANING SOLVENT</b>	White Spirit or Xylene
-------------------------	------------------------

<b>PACKING</b>	5 litre tins or 25 litre drums
----------------	--------------------------------

Important

*Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.*

*Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (Certificate No. FM01548).*

**Winn & Coales (Denso) Ltd**  
 Denso House, Chapel Road,  
 London SE27 0TR, United Kingdom



**Tel: +44 (0) 20 8670 7511**  
**Fax: +44 (0) 20 8761 2456**  
**Email: mail@denso.net Web: www.denso.net**