



DENSO SELF ADHESIVE PVC TAPE

- DESCRIPTION** As an outerwrap for Denso petrolatum tapes, Densoclad and Densopol bituminous tapes.
- COMPOSITION** Plasticised PVC sheeting coated one side with a rubber resin pressure sensitive adhesive. Supplied self-wound in rolls.

TYPICAL PROPERTIES	DATA
Colour	Yellow or Black
Adhesion <i>To Self</i> <i>To Steel</i>	2.5 N/cm 3.5 N/cm
Breaking Load	35 N/cm
Tensile Strength	18 N/mm ²
Elongation at Break	150% minimum
50% Modulus	9.0 N/mm ²
Temperature Range <i>For Application</i> <i>For Service</i>	0°C to 60°C 80°C maximum
Breakdown Voltage	16 kV minimum per double layer
Roll Length	33m
Roll	25mm, 50mm, 75mm 100mm, 150mm
Thickness	0.19mm
Weight	0.25kg/m ²

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd
 Denso House, Chapel Road,
 London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511
Fax: +44 (0) 20 8761 2456
Email: mail@denso.net Web: www.denso.net